

MANLY

As with all quality carpets, slight variation in colour may vary from dye lot to dye lot. It is recommended that this carpet be laid in accordance with AS2455. Seam Sealer must be used on all seams. For conventional installation heavy duty underlay is recommended. Alternatively, a dual bond or direct stick installation can be used.

Protective chair pads are recommended under office chairs with roller casters to preserve the appearance and avoid premature wear. Professional cleaning is recommended. Construction of this carpet may involve the occurrence of shading. Certain light sources shining across the surface may emphasise the effect of shading. Shading is not a manufacturing defect and will not detract from the carpet performance. Since carpet is a textile material, a perfect pattern match on the linear pattern cannot be guaranteed.

George Low reserves the right to modify specifications subject to manufacturing variances. Manufacturing processes may necessitate specification changes without prior notice and without prejudice.

Made in Australia

Pile Fibre	100% BCF SD Polypropylene
Yarn Structure	UV Stabilised Loop Pile
Colouration	Solution Dyed
Machine Gauge	1/10
Pile Height	4 mm approx.
Width	3.66 m
Tufted Pile Weight	20 oz/yd ² . 678 g/m ²
Primary Backing	Woven Synthetic
Secondary Backing	Jute
Average Tuft Bind	Exceeds C.I.A. requirements AS2111.15
Backing Bond Strength	Exceeds C.I.A. requirements AS2111.16
Pattern Repeat	40 cm x 40 cm approx.
Fire Rating	ASISO 9239.1-2003
CHF Value	1.3 kW/m ²
Smoke Value	148 % min
Rating	Residential Heavy Duty

- Warranties/Features**
- **5 Year Limited Wear**
 - **Solution Dyed**
 - **Hidden Graphic**

George Low of Melbourne Pty Ltd

Telephone: (03) 9587 4222 Facsimile: (03) 9587 4525 www.georgelow.com.au sales@georgelow.com.au