GeorgeLow

ΜΙΝΤΟ

ΜΙΝΤΟ

As with all quality carpets, slight variation in colour may vary from dye lot to dye lot. It is recommended that this carpet be laid in accordance with AS2455. Seam Sealer must be used on all seams. For conventional installation heavy duty underlay is recommended. Alternatively, a dual bond or direct stick installation can be used. Protective chair pads are recommended under office chairs with roller casters to preserve the appearance and avoid premature wear. Professional cleaning is recommended. Construction of this carpet may involve the occurrence of shading / permanent pile reversal. Certain light sources shining across the surface may emphasise the effect of shading / permanent pile reversal. This occurrence cannot be predicted or prevented - it is not a manufacturing defect and will not detract from the carpet performance. Since carpet is a textile material, a perfect pattern match on the linear pattern cannot be guaranteed.

George Low reserves the right to modify specifications subject to manufacturing variances. Manufacturing processes may necessitate specification changes without prior notice and without prejudice.

Made in Australia

Pile Fibre	100% Wool
Yarn Structure	Woolen Spun R900/2
Colouration	Yarn Dyed
Machine Gauge	5/32
Pile Height	9.5 mm approx.
Width	3.66 m
Tufted Pile Weight	50 oz/yd2. 1695 g/m2
Primary Backing	Woven Synthetic
Secondary Backing	Jute
Insect Resistance	To Australian Standard
Average Tuft Bind	Exceeds C.I.A.
	requirements
	AS2111.15
Backing Bond Strength	Exceeds C.I.A.
	requirements
	AS2111.16
Fire Rating	ASISO 9239.1-2003
CHF Value	On Application
Smoke Value	On Application
Pattern Repeat	None
Rating	Residential Extra
	Heavy Duty
	and Stairs
	Commercial Heavy
	Duty
	Duty

- Warranties/Features Hea
 - Heavy Textured Twist
 Contemporary Tones
 - 100% New Zealand Wool

George Low of Melbourne Pty Ltd

Telephone: (03) 9587 4222 Facsimile: (03) 9587 4525 www.georgelow.com.au sales@georgelow.com.au