


# ORIGIN

4 METRE



Diverse selection of best-selling designs  
2.6 mm thick with 0.25 mm wear layer  
Excellent 19 dB sound reduction  
Extra resistant to scuffs, scratches and stains  
10-year warranty







Vinyl floor Covering	EN ISO 26986
Classes of Use	EN ISO 10874 








## PRODUCT ID

 Total Thickness	EN ISO 24346	2,60 mm	 Impact Sound Absorption	EN ISO 717-2	19 dB
 Wear Layer Thickness	EN ISO 24340	0,25 mm	 Residual Indentation	EN ISO 24343-1	≤ 0,35 mm
 Weight	EN ISO 23997	1,690 kg/m <sup>2</sup>	Wear Layer Binder content	ISO 11638	Type I
 Roll Width	EN ISO 24341	4m			
 Roll Length		30 m			

## PRODUCT SAFETY & SECURITY CHARACTERISTICS

 Slip Resistance	EN 13893 DIN 51130	μ ≥ 0,30 R10	 Fire Classification	EN 13501-1	Cfl-S1
 Static Electrical Propensity	EN 1815	≤ 2 kV	 Chemical Resistance	EN ISO 26987	Not Affected*

## PRODUCT ENVIRONMENTAL BEHAVIOR

 Dimensional Stability	EN ISO 23999	≤ 0,40 %	 PHTHALATE FREE Technology *Except recycled content	 Better Indoor Air Quality *TVOC AT 28 DAYS < 100 μg/m <sup>3</sup>	 100 % Recyclable	 ÉMISSIONS DANS L'AIR INTÉRIEUR A+ A B C
 Thermal resistance for underfloor heating	ISO 10456 EN 12524-1	0,04 m <sup>2</sup> /kW				
 Light Fastness	EN ISO 105 B02	≥ 6				

\*For short-term exposure of dilute acids, oils and fats, no change in the material properties.



# George Low

114-118 Woodlands Drive,  
Braeside VIC 3195  
03-95814222