

Bulletin Board®

Technical specifications



green building council australia
MEMBER



Transparent.
Quantified.
Global.

	Total Thickness	EN-ISO 24346	6.0 mm ± 0.25 mm
	Roll Width	EN-ISO 24341	1.22 m (3 colours in 1.83 m)
	Roll Length	EN-ISO 24341	≤ 28 m
	Total Weight	EN-ISO 23997	4.7 kg/m ² ± 10%
	Flexibility	EN-ISO 24344	Ø 50 mm, according to method A
	Sound absorption coefficient	EN-ISO 354	α _w 0.1 (typical)
	Thermal conductivity	EN 12524	0.10 W/m-K
	Self-healing properties	LH000420	yes
	Force on pins - Perpendicular to pin direct	LH000421	25 N (typical)
	Force on pins - Perpendicular to pin at 7 mm	LH000421	10 N (typical)
	Force on pins - Parallel to pin (pulling the pin out)	LH000421	15 N (typical)
	Bacteriostatic properties	EN-ISO 22196	yes
	Chemical resistance	EN-ISO 26987	Resistant to diluted acids, oils and the most conventional solvents such as alcohol, white spirit, etc. Not resistant to prolonged exposure to alkalis.
	Dimension stability		Due to the natural jute back, providing a strong durable foundation, the product is dimensionally stable in all directions when properly installed. It resists cracking, drying and peeling.
	Reaction to fire	AS 4586	Group 3
	Anti-static		yes
	Gloss		Only available in matt colors, so that reflection caused by sunlight or artificial light is reduced.
	Natural materials (e.g. cork, linseed oil, jute)		91%
	Recycled content		43%
	PVC, PET, plasticizers content		0%

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.
All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.



Declare.

Bulletin Board Forbo Flooring Systems

Final Assembly: Assendelft, Netherlands
Life Expectancy: 25 Years
End of Life Options: Recyclable (100%)

Ingredients:

Binder: Linseed Oil (USA), Gum Rosin; **Filler:** Cork (Portugal), Calcium Carbonate; **Pigment:** Titanium Dioxide; **Backing:** Jute Fiber

Living Building Challenge Criteria:

FRB-0003 Exp: 03/01/2016
VOC Optimize: N/A VOC Emissions: CDPH Compliant
Declaration Status LBC Red List Free
 LBC Compliant
 Declared

MANUFACTURER RESPONSIBLE FOR LABEL ACCURACY
INTERNATIONAL LIVING FUTURE INSTITUTE™ declareproducts.com

Australia

Forbo Flooring Systems Pty Ltd.
23 Ormsby Place
Wetherill Park
NSW 2164
Tel: +61 2 9828 0200
Free Call 1800 224 471
Fax: +61 2 9825 3456
info.au@forbo.com
www.forbo-flooring.com.au

New Zealand

Inzide Commercial Ltd
52B Arrenway Drive
Rosedale 0632
Auckland New Zealand
Tel: +64 9 441 9850
Free Call 0800 800 656
Fax: +64 9 441 9851
enquiries@inzide.co.nz
www.inzide.co.nz

Distributed by

VIC/TAS/SA

George Low Pty Ltd
114-118 Woodlands Drive
Braeside VIC 3195

Tel: 03 9587 4222
Fax: 03 9587 4525
www.georgelow.com.au
sales@georgelow.com.au

QLD/NSW

PR Floors
21 Computer Rd
Yatala QLD 4207

T: 07 3807 4422
F: 07 3807 4451
sales@prfloors.com
www.prfloors.com