





Technical specifications

^	Total thickness	EN ISO 24346	2.0 mm
	Collection size		24
	Roll width	EN ISO 24341	1.83 m
	Roll length	EN ISO 24341	≤ 30 m
	Total weight	EN ISO 23997	2100 g/m ²
	Residual indentation	EN ISO 24343-1	≤ 0.20 mm
77	Colour fastness to light	EN ISO 105-B02 method 3	≥6
	Gloss level	ISO 2813	<5
52	Flexibility	EN-ISO 24344	ø 50 mm
$ \ \ \ \ \ \ \ \ $	Resistance to chemicals	EN ISO 26987	Resistant to diluted acids, oils, fats and to the conventional solvents. Not resistant to prolonged exposure to alkalis.
3333	Heat resistance		70°C
% 20W	Antistatic	EN 1815	≤ 2.0 kV
Ø	Reaction to fire	AS 5637.1	Group 3
∞	Creating better environments		LCA is the foundation for securing the lowest environmental impact Furniture Linoleum is climate positive cradle to gate*
	Natural materials		Made with 94% natural ingredients (e.g. linseed oil, rosin, wood flour). Contains PEFC certified wood flour. Contains FSC certified paper.
0	Recycled content		$Contains ingredients derived from \ recycled \ sources \ coming \ from \ post-industrial \ streams.$
	Health and safety		REACH compliant to assure human safety and health.
	Renewable electricity		Manufactured using 100% electricity from renewable sources.
_	Green certifications		Declare Red List Free and third-party verified EPD

^{*} For details, please consult the Furniture Linoleum EPD.

 $Furniture\ Linoleum\ is\ a\ natural\ product, so\ there\ can\ be\ slight\ colour\ variations\ in\ different\ batches.$

All Forbo Flooring Systems' sales organisations worldwide have a certified Quality Management System in accordance with ISO 9001.

All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.

The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) which can be found on all of our websites. Furniture Linoleum is manufactured at an SA8000 ° - certified organisation.



