

D@N5 F-6 UbX'J9 @CI F

As with all quality carpets, slight variation in colour may vary from dye lot to dye lot. It is recommended that this carpet be laid in accordance with AS2455. Seam Sealer must be used on all seams. For conventional installation heavy duty underlay is recommended. Alternatively, a dual bond or direct stick installation can be used. Protective chair pads are recommended under office chairs with roller casters to preserve the appearance and avoid premature wear. Professional cleaning is recommended. Construction of this carpet may involve the occurrence of shading / permanent pile reversal. Certain light sources shining across the surface may emphasise the effect of shading / permanent pile reversal. This occurrence cannot be predicted or prevented – it is not a manufacturing defect and will not detract from the carpet performance. Since carpet is a textile material, a perfect pattern match on the linear pattern cannot be guaranteed.

George Low reserves the right to modify specifications subject to manufacturing variances. Manufacturing processes may necessitate specification changes without prior notice and without prejudice.

Made in Belgium

George Low of Melbourne Pty Ltd

Pile Fibre	100% PP
Colouration	Solution Dyed
Pile Height	7.0 - 10.0 mm Approx.
Width	2.00 metre
Tufted Pile Weight	1,000 g/m2. +/- 5%
PrcXi WimdY	Non woven
K YUf`K UffUblmi-bXccf	5 year
K YUf`K UffUblmiCi hXccf	3 Year

Features	<ul style="list-style-type: none"> • Contemporary Colours • Solution Dyed PP • Velour or Rib Pile
-----------------	---